

## Technical Information Fluorescent Lacquer



MoTip Fluorescent Spray gives the user utmost visibility and safety. It can be used to mark dangerous spots and increase attention to motorbikes or bicycles.

It is suitable for metal, wood, aluminium, glass, stone and most plastics.

Apply a base layer of MoTip white primer for optimum brightness.



### Quality and properties

---

- Top acrylic quality
- Excellent adhesion on numerous materials
- Good flow, flat surface
- Fast drying time
- Smear proof
- Weatherproof
- Partially lightfast and UV resistant. Intense brilliance of colours fades with time. Top coating with a clear lacquer slows down this process.
- Scratch, shock and impact proof

### Physical and chemical data

---

- **Basis of the binder:** Acrylic copolymeres
- **Colour:** diverse
- **Smell:** solvent
- **Degree of gloss** (at measurement angle 60° acc. to DIN 67530):  
matt: 5-10 gloss units
- **Efficiency:**  
Depending on consistence and color of the ground:  
400 ml are sufficient for approx. 0.8 - 1.0 m<sup>2</sup>
- **Drying time (at 20°C, 50% relative air humidity):**  
Dust-dry: after approx. 15 minutes  
Dry to touch: after approx. 30 minutes  
Coatable: after approx. 1 - 2 hours  
The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- **Temperature-resistant:** up to 80°C
- **Storage stability:**  
10 years if appropriate storage provided  
(=10°-25°C, relative air humidity of max. 60%)
- **Size:**  
aerosol can with maximum nominal volume 400 ml

### Environment and labelling

---

**Environmentally sound:** The products of MOTIP DUPLI are 100% free of heavy metals. The caps and packagings are made of recyclable material.

**Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling:** All products made by MOTIP DUPLI comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

### Instruction manuel

---

**Before use, carefully read and observe the warning texts on the label!**

#### Application:

- The surface should be clean, dry and free of grease.
-

- Sand off old paintwork and coated parts.
- Cover areas not to be treated with masking tape.
- Pre-prime with MoTip white primer. Once it has dried, sand smooth with sandpaper.
- Shake can for 2 minutes before use.
- Spray to test compatibility on an inconspicuous area.
- Spray several thin coats from a distance of 25 cm crosswise.
- The intensity of the shine fades with time. A clear lacquer coating slows this process.
- Do not spray on surfaces coated with synthetic resin!

### **Tips for spray painting**

---

Protect the object and the surrounding area from spray mist. When painting small areas it is recommended that a piece of card is used as a mask, with a hole cut in it slightly larger than the area to be sprayed. The mask should be held 1 to 2 cm from the surface. With this method, the mainly part of the spray mist is brought under control. It recommends to mask parts not to be lacquered, to protect the surrounding against the spray mist.

The aerosol can should have room temperature.

Temperature should range between +10°C and +25°C, max. air humidity 60 %.

Store in a dry place. Protect from direct sunlight and other sources of heat. Use only during dry weather, in places protected from the wind, and in well-ventilated rooms. Follow the warning texts on the labels!

### **Disclaimer of liability**

---

This application-technological information is given to the best of our knowledge. The notes mentioned herein are, however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. MOTIP DUPLI is let off the liability, unless the liability-based incident is caused by a fault incurred to MOTIP DUPLI.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 8h a.m. to 5 h p.m. or on Friday until 12 h p.m.

As of: February 8, 2010

This release replaces all eventually earlier issued versions.

Print date: 19.05.2013

MOTIP DUPLI GmbH | Kurt-Vogelsang-Straße 6 | 74855 Haßmersheim | [info@dupli-color.de](mailto:info@dupli-color.de)